

DESCRIPTION

Designed for exclusive use with the 9000M2 Series amplifier, the ZM-9014 is a wall mounted remote control panel having 4 buttons and 1 volume control knob. It is used in conjunction with the RC-001T Remote control module.

Scene switching and paging ON/OFF functions can be assigned to the buttons, and input or output channel's volume adjustment to the volume control knob.

It can be mounted in an American standard 2-gang electrical box in the wall.

SPECIFICATIONS

| | |
|-----------------------|---|
| Power Source | 24 V DC (supplied from RC-001T) |
| Current Consumption | 50 mA or less |
| Terminal | Removable terminal block (10 pins) |
| Connection Cable | Shielded CPEV cable (paired data line and paired power line) or Category 5 twisted pair cable for LAN (CAT5-STP) |
| Operating Section | 4 function buttons, 1 volume control |
| Indicator | 4 function indicators (green LEDs), Level indicators (green LEDs) |
| Operating Temperature | 0 °C to +40 °C (32 °F to 104 °F) |
| Operating Humidity | 35 % to 80 %RH (no condensation) |
| Finish | Surface-treated steel plate, white, paint |
| Dimensions | 120 (W) × 127 (H) × 58.5 (D) mm (4.72" × 5" × 2.3") |
| Weight | 300 g (0.66 lb) |
| Accessory | Box mounting screw (No.6-32UNC × 30) ×4, Box mounting screw (M4 × 30) ×4, Panel mounting screw ×4, Removable terminal plug (10 pins) ×1 |

Note: Since no electrical box is supplied with the unit, prepare it separately.

APPEARANCE

