



BS-680 Series

Public Address Speakers



Innovative design based on the Golden Ratio.

Features

- Quick and easy installation
- Strong all-metal body
- Horizontal / vertical installation
- Wall / in-wall mounting
- Ideally suited for voice alarm system application
- Two statite screw terminal blocks and thermal fuse
- BS-680U is UL 1480 UUMW rated



Specifications

	BS-680FC	BS-680U
Rated Input	6W (100V line)	6W (70V line)
Rated Impedance	100V line: 1.7k Ω , 3.3k Ω , 6.7k Ω , 13k Ω 70V line: 1.7k Ω , 3.3k Ω , 6.7k Ω , 13k Ω	70V line: 830 Ω (6W), 1.67k Ω (3W), 5k Ω (1W) 25V line: 150 Ω (6W), 210 Ω (3W), 650 Ω (1W)
Sensitivity (1W, 1m)	96 dB	94 dB
Frequency Response	150 – 20.000 Hz	
Speaker Component	16cm/6.3" double cone-type	
Finish	Enclosure: Steel plate, off-white Grille: Stainless steel punching net, off-white	
Dimensions	310(W) x 190(H) x 90(D) mm 12.2(W) x 7.48(H) x 3.54(D)in	
Weight	2.6kg / 5.73lbs	