

### DESCRIPTION

TOA's F-505WP-L is a splash-proof two-way speaker system for low-impedance line, and is made up of a 20 cm woofer and a constant directivity horn with a driver.

### SPECIFICATIONS

Enclosure	Sealed enclosure
Power handling Capacity	Continuous pink noise: 80 W Continuous program: 240 W
Rated Impedance	8 Ω
Sound Pressure Level	93 dB (1 W, 1 m)
Frequency Response	80 - 20,000 Hz
Crossover Frequency	3,500 Hz
Speaker Component	Low frequency: 20 cm dia cone speaker High frequency: CD horn fitted with driver (60° horizontal × 40° vertical)
Connected Cable	Cable sent straight from internal speaker: 6.6 mm in diameter, Conductor cross section: 0.75 mm <sup>2</sup> , 2-core cable, 2 m
Finish	Enclosure: Polypropylene resin, ivory Front grill: Stainless steel, ivory, paint
Dimensions	452 (W) × 282 (H) × 210 (D) mm
Weight	9 kg
Usable Optional Mounting Bracket	Wall mounting: YS-500, YS-60 Pole mounting: YS-500 + YS-60B (pole diameter: 90 - 340 mm) : YS-60 + YS-60B (pole diameter: 90 - 340 mm)

Note: Exterior case is not treated with corrosion-free paint.

### APPEARANCE

