

DESCRIPTION


The M-01P is a microphone input module to be used in conjunction with the 900 series components and other TOA's equipment. It has a transformer balanced microphone input with  $\phi 6.3$  (1/4") phone jack connector, phantom power supply function, and gain and tone controls.

SPECIFICATIONS

\* 0 dB=1 V


Power Source	24 V DC (supplied from the main frame)
Current Consumption	9 mA
Input Sensitivity	-60 dB* (rated output: -20 dB*), adjustable: -72 to -52 dB*
Input Impedance	600 $\Omega$ , balanced
Frequency Response	25 Hz - 20 kHz $\pm 2.0$ dB
Distortion	0.05 % or less (1 kHz, output: 0 dB*)
Noise Level	-86 dB* (20 Hz - 20 kHz BPF), input equivalent noise: -126 dB*
Gain	32 - 52 dB
Phantom Power	+22 V DC (active or disable selectable)
Tone Control	100 Hz: 0 to -10 dB, 10 kHz: 0 to -10 dB
Connector	$\phi 6.3$ (1/4") Phone jack (3P)
Dimensions	35 (W) x 78 (H) x 88 (D) mm (1.38" x 3.07" x 3.46")
Weight	Max. 110 g (0.24 lb)

APPEARANCE



Front View

Side View



Connection Diagram

UNIT:mm SCALE:1/1